



COMMON PVF ABBREVIATIONS

MATERIALS	
<b>A105NLC</b>	Normalized Low Carbon
<b>CI</b>	Cast Iron
<b>CS</b>	Carbon Steel
<b>GALV</b>	Galvanized
<b>HDG</b>	Hot Dip Galvanized
<b>RTFE</b>	Reinforced Teflon

  

PIPE	
<b>BE</b>	Beveled Ends
<b>BEV</b>	Beveled Ends
<b>DSAW</b>	Double Submerged Arc Welded
<b>ERW</b>	Electric resistance welded
<b>S160</b>	Schedule 160
<b>S20</b>	Schedule 20
<b>SMAW</b>	Shielded metal arc welded
<b>SMLS</b>	Seamless
<b>STD</b>	Standard
<b>THD</b>	Threaded Ends
<b>XH</b>	Extra Heavy
<b>XS</b>	Extra Strong
<b>XXH</b>	Double Extra Heavy
<b>XXS</b>	Double Extra Strong

  

VALVES	
<b>BB</b>	Bolted Bonnet
<b>BC</b>	Bolted Cap
<b>BW</b>	Butt Weld
<b>CONV</b>	Conventional Bore
<b>FP</b>	Full Port
<b>IS&amp;S</b>	Inside Screw and Stem
<b>OS&amp;Y</b>	Outside Screw & Yoke
<b>PS</b>	Pressure Seal
<b>RP</b>	Reduced Port
<b>SL</b>	Spring Loaded
<b>SP</b>	Standard Port
<b>WB</b>	Welded Bonnet
<b>WOG</b>	Water Oil Gas



COMMON PVF ABBREVIATIONS

NIPPLES	
<b>BLE</b>	Beveled Large End
<b>BOE</b>	Beveled One End
<b>PBE</b>	Plain Both Ends
<b>POE</b>	Plain One End
<b>PSE</b>	Plain Small End
<b>PXT</b>	Plain By Threaded
<b>TBE</b>	Threaded Both Ends
<b>TOE</b>	Threaded One End

FITTINGS	
<b>CONC</b>	Concentric
<b>ECC</b>	Eccentric
<b>FF</b>	Flat Face
<b>LR</b>	Long Radius
<b>RED</b>	Reducing
<b>RF</b>	Raised Face
<b>SR</b>	Short Radius
<b>SW</b>	Socket Weld
<b>THD</b>	Threaded

GENERAL	
<b>+ AML</b>	Approved Manufacturer
<b>DURO</b>	Durometer
<b>FLEX</b>	Flexible
<b>NPT</b>	National Pipe Thread
<b>PC</b>	Piece
<b>PSI</b>	Pounds/Square Inch
<b>PSIG</b>	PSI At The Gauge
<b>PVF</b>	Pipe Valve Fitting
<b>TPI</b>	Teeth Per Inch